L Number	Hits	Search Text	DB	Time stamp
-	6417533	transcod$5 or interpret$5 or cod$5 or struct$5 or sequenc$5 or translat$5 or encod$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:50
-	5469506	messsag$5 or signal$5 or data	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:50
-	11817431	field or type or bin or section or portion or part or pars$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:51
-	6872264	cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:53
-	6806295	transmit$5 or transmission or send$5 or transfer$5 or deliver$5 or provid$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:54
-	1445069	destination or client or subscber or user	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:54
-	9214197	device or computer or PALM or PDA or phone or mobile or terminal or workstation or station	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:55
-	3489872	source or server or master or host or company or provider	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:55
-	4877027	receiv$5 or collect$5 or reception	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:02
-	4493250	deriv$5 or caluclat$5 or determin$5 or justif$5 or configur$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:57
-	5584024	second or subsequent or next	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:57
-	3643262	maintain$5 or keep$5 or unalter or unmodif$5 or unchang$5 or original	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:58
-	5876931	first or initial or primary or orignal	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:58
-	4511469	change$5 or modif$5 or alter$5 or updat$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:59

–	800617	omit$5 or ignor$5 or delet$5 or skip$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 13:59
–	10328569	cod$5 or key$5 schem$5 or encrypt$5 or cipher$5 or function$5 or algorith or method or schem$5	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:01
–	253673	(transcod$5 or interpret$5 or cod$5 or struct$5 or sequenc$5 or translat$5 or encod$5) with (messsag$5 or signal$5 or data) with (field or type or bin or section or portion or part or pars$5)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:12
–	1045321	(cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (field or type or bin or section or portion or part or pars$5)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:21
–	178698	(transmit$5 or transmission or send$5 or transfer$5 or deliver$5 or provid$5) with (destination or client or subscber or user) with (device or computer or PALM or PDA or phone or mobile or terminal or workstation or station)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:26
–	985558	(device or computer or PALM or PDA or phone or mobile or terminal or workstation or station) with (source or server or master or host or company or provider)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:31
–	15790	(deriv$5 or caluclat$5 or determin$5 or justif$5 or configur$5) with (cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (maintain$5 or keep$5 or unalter or unmodif$5 or unchang$5 or original)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:34
–	41956	(deriv$5 or caluclat$5 or determin$5 or justif$5 or configur$5) with (cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (change$5 or modif$5 or alter$5 or updat$5)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:41
–	8998	(deriv$5 or caluclat$5 or determin$5 or justif$5 or configur$5) with (cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (omit$5 or ignor$5 or delet$5 or skip$5)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 14:46

–	64	((transcod$5 or interpret$5 or cod$5 or struct$5 or sequenc$5 or translat$5 or encod$5) with (messsag$5 or signal$5 or data) with (field or type or bin or section or portion or part or pars$5)) and ((cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (field or type or bin or section or portion or part or pars$5)) and ((transmit$5 or transmission or send$5 or transfer$5 or deliver$5 or provid$5) with (destination or client or subscber or user) with (device or computer or PALM or PDA or phone or mobile or terminal or workstation or station)) and ((deriv$5 or caluclat$5 or determin$5 or justif$5 or configur$5) with (cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (maintain$5 or keep$5 or unalter or unmodif$5 or unchang$5 or original)) and ((deriv$5 or caluclat$5 or determin$5 or justif$5 or configur$5) with (cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (change$5 or modif$5 or alter$5 or updat$5)) and ((deriv$5 or caluclat$5 or determin$5 or justif$5 or configur$5) with (cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (omit$5 or ignor$5 or delet$5 or skip$5))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 15:27
–	10962	(((transcod$5 or interpret$5 or cod$5 or struct$5 or sequenc$5 or translat$5 or encod$5) with (messsag$5 or signal$5 or data) with (field or type or bin or section or portion or part or pars$5)) and ((cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (field or type or bin or section or portion or part or pars$5)) and ((transmit$5 or transmission or send$5 or transfer$5 or deliver$5 or provid$5) with (destination or client or subscber or user) with (device or computer or PALM or PDA or phone or mobile or terminal or workstation or station))) and @ad<19991214	USPAT	2004/07/21 15:29
–	78	transcod$5 and (hash$ with function)	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 15:29
–	17	(((((transcod$5 or interpret$5 or cod$5 or struct$5 or sequenc$5 or translat$5 or encod$5) with (messsag$5 or signal$5 or data) with (field or type or bin or section or portion or part or pars$5)) and ((cod$5 or key$5 or identif$5 or ID or nam$5 or tag$5 or mark$5) with (field or type or bin or section or portion or part or pars$5)) and ((transmit$5 or transmission or send$5 or transfer$5 or deliver$5 or provid$5) with (destination or client or subscber or user) with (device or computer or PALM or PDA or phone or mobile or terminal or workstation or station))) and @ad<19991214) and (transcod$5 and (hash$ with function))	USPAT; US-PGPUB; EPO; JPO; DERWENT; IBM_TDB	2004/07/21 15:29